



WIDTH/ LENGTH	WEIGHT	BASE PRODUCT CODE	MSRP
7X14	1,160#	7X14ODTA35	
7X16	1,265#	7X16ODTA35	
7X18	1,355#	7X18ODTA35	

* Shown w/ optional 2 5/16 Coupler (5,000# GVWR)

HIGHLIGHTS

- Perimeter Tube Frame
- 3" x 6" Extruded Alum. Triple Tongue Design
- ATP Fenders w/ Gussets
- Surface Mount L.E.D. Lighting
- Pressure Treated Prime Decking
- Fold-In Radius Gate
- Stake Pockets
- 2" x 4" Tube Rear Gate Supports

	STANDARD FEATURES		POPULAR OPTIONS			
				MSRP		MSRP
STRUCTURAL						
Cross Members	2" x 3" Tube 24" OC	16" OC			12" OC	
Frame	2" x 4" Perimeter Tube					
Jack	2,000# Top-Wind Set Back Jack w/ Foot	Ultimate Adj. 2K Jack w/Foot			5,000# Jack w/ Foot	Caster Wheel ILO Foot
Rear Loading	48" Fold-In Radius Tube Gate	48" Bi-Fold Square Gate ILO Straight			60" Bi-Fold Square Gate ILO Straight	
Sides	1.5" x 1.5" Tube 14" Tall	24" Sides ILO 14"			14" ATP Skirting .045	24" ATP Skirting .125
Side Loading	<i>Optional</i>	53" Radius Side Gate			53" Bi-Fold Square Gate	
Tongue	3" x 6" Extruded Alum. Triple Tongue					
Top Rail	2" x 2" Tube					
RUNNING GEAR						
Axles	3,500# E-Z Lube 4" Drop Spring 1 Electric Brake & 1 Idler	Add 2nd Brake			Torsion Axles (2 Brakes)	
Tires/ Wheels	ST205/75R14 Nitrogen Filled Silver Mod Steel	ST205/75R14 Spare Tire	Alum- Steel		Spare Mount	Aluminum Wheels Upgrade
FLOORS						
Floor	Dura Color Prime Dimensional Pine	Extruded Aluminum				
COMPONENTS						
Coupler	2" Straight	2 5/16" Straight			Adjustable Coupler	
Stake Pockets	Included	Additional Stake Pockets				
Tie Downs	<i>Optional</i>	1,000# D-Rings (Installed)			5,000# D-Rings (Installed)	