



* Shown w/ optional Alum. Wheel Upgrade & Extruded Aluminum Floor

WIDTH/ LENGTH	WEIGHT	BASE PRODUCT CODE	MSRP
7X16	1,226#	7X16OCHTA35	
7X18	1,346#	7X18OCHTA35	
7X20	1,405#	7X20OCHTA35	
7X22	1,525#	7X22OCHTA35	
*7X24	1,655#	7X24OCHTA52	

* Standard w/ 5,200# Axles & ST225/75R15, 6-Bolt Tires

HIGHLIGHTS

- 32" Beavertail (18' - 24')
- Triple Tube A-Frame Steel Reinforced Tongue
- ATP Fenders w/ Gussets
- Surface Mount L.E.D. Lighting
- Rub Rail
- Stake Pockets
- Front Mounted Ramps
- Tubing Bump Rail

STRUCTURAL	STANDARD FEATURES		POPULAR OPTIONS			
			MSRP		MSRP	MSRP
Cross Members	2" x 3" Tube 16" OC	12" OC				
Frame	2" x 6" Tube					
Jack	2,000# Top-Wind A-Frame Jack w/ Foot	Ultimate Adj. 2K Jack w/Foot		5,000# Jack w/ Foot		7,000# Drop-Leg Jack w/ Foot
Rear Loading	12" x 82" Aluminum Ramps (Front Mounted)					
Side Loading	N/A	Removable Fender(s)				
Tongue	2" x 6" Tube w/ Steel Reinforcement					
Top Rail	2" Tube Bump Rail					
RUNNING GEAR						
*Axles	3,500# E-Z Lube Torsion, 2 Electric Brakes (16'-22')	5,200# w/ 225 Tires (6-Bolt) (Standard on 24')		7,000# w/ 235 Tires (8-Bolt) (16'-22') (24')		Spread Axles
Tires/Wheels	ST205/75R15 Nitrogen Filled Silver Mod Steel	ST205/75R15 Spare Tire	Alum. Steel	Spare Mount		Aluminum Wheels Upgrade
FLOORS						
Beavertail	32" (18' - 24')	No Beavertail (Std on 16')				
Floor	Dura Color Prime Dimensional Pine	Extruded Aluminum				
COMPONENTS						
Coupler	2 5/16" A-Frame	Adjustable Coupler		Adjustable Pintle		
Stake Pockets	Included w/ Rub Rail					
Storage	Optional					
Tie Downs	4-5,000# D-Rings (Installed)	Additional 5,000# D-Rings (Installed)				